

Please amend the application as follows:

In the Specification

Please amend the title of the application to read as follows:

MAINTENANCE OF CHANNEL USAGE IN A WIRELESS COMMUNICATION SYSTEM

In the Claims

Please cancel claims 13-35.

Please amend claims 1-12. Amendments to the claims are indicated in the attached  
"Marked Up Version of Amendments" (pages i - iii).

Sub B1  
A1  
Con

1. (Amended) A method for accessing data from a network via a wireless communication link, the method comprising the steps of:

at a subscriber transceiver in an idle mode when no channels are allocated for sending payload data, determining whether at least a portion of payload data has been received from a computer device, the payload data intended to be transmitted over the wireless communication link;

in response to detecting a presence of the payload data, requesting use of a first set of traffic channels by sending a traffic channel allocation request message, the first set of traffic channels including at least one traffic channel that the subscriber transceiver uses to transmit the payload data over the wireless communication link to a base station transceiver; and

transmitting the payload data over the first set of traffic channels to the base station transceiver.

2. (Amended) The method of claim 1, wherein the payload data is transmitted via Code Division Multiple Access (CDMA) modulated radio signals.
3. (Amended) The method of claim 1, further comprising:

transmitting a message to release the first set of traffic channels after the payload data is transmitted.

4. (Amended) The method of claim 3, further comprising:  
receiving an assignment of a second set of traffic channels, the second set of traffic channels including at least one traffic channel; and  
receiving payload data over the second set of traffic channels.

5. (Amended) The method of claim 3, wherein the first set of traffic channels is released based upon a request message from the subscriber transceiver.

6. (Amended) A method for accessing data from a computer network via a wireless communication link, the method comprising the steps of:

constructing a first set of at least one traffic channels to transmit a data payload from a remote transceiver to a base station;

at the base station, receiving the data payload over the at least one traffic channels of the wireless communication link;

generating a message from the remote transceiver requesting a release of the first set of traffic channels after determining that the payload data has been transmitted to the base station; and

after the at least one traffic channels is released, maintaining an idle mode between a remote transceiver and a base station without an allocation of traffic channels to support data payload transfers, the idle mode being supported by sending timing information over a low-bandwidth non-traffic channel.

7. (Amended) The method of claim 6, wherein a request for information related to a network address is received over Code Division Multiple Access (CDMA) modulated radio signals.

8. (Amended) The method of claim 6, further comprising the steps of:

BI  
Cano -  
sending an assignment of a second set of at least one traffic channels; and  
sending data associated with a network address over the second plurality of traffic channels.

9. (Amended) The method of claim 1 further comprising:  
receiving a request for additional traffic channels.
10. (Amended) The method of claim 8, wherein said sending an assignment of a second set of traffic channels is achieved by sending the message on a forward control or non-traffic channel.
11. (Amended) The method of claim 9, wherein the request for additional traffic channels is received over a reverse control or non-traffic channel.
12. (Amended) The method of claim 9, wherein the request for additional traffic channels includes information including a number of channels needed.
- cont

Sub B17  
Cont.  
Please add new Claim(s) 36-49 .

36. (New) A method to support communication of information over a wireless link, the method comprising:  
while in an idle mode when no traffic channels are assigned for use to transmit payload data information to a target transceiver, detecting a presence of at least part of a data payload at a subscriber transceiver for transmission over the wireless link to the target transceiver;  
generating a request message from the subscriber transceiver to the target transceiver for an assignment of one or multiple traffic channels to transmit the data payload; and

*B1  
Cand* in response to receiving the request message from the subscriber transceiver, assigning one or more traffic channels for use by the subscriber transceiver to transmit the data payload to the target transceiver over the wireless link.

37. (New) A method as in claim 36 further comprising:

transmitting the data payload from the subscriber transceiver to the target transceiver; and

at the target transceiver, receiving a message from the subscriber transceiver indicating a request to release traffic channels.

38. (New) A method as in claim 37 further comprising:

from the target transceiver, transmitting a message to the subscriber transceiver indicating that traffic channels are being deallocated.

*A1  
Cont* 39. (New) A method as in claim 36, wherein the step of assigning traffic channels includes:

sending a message from the target transceiver to the subscriber transceiver indicating traffic channels to be used to transmit the data payload.

40. (New) A method as in claim 36, wherein the target transceiver is a base station transceiver communicating with multiple subscriber transceivers.

41. (New) A method as in claim 36, wherein low-bandwidth timing signals are transmitted from the subscriber transceiver to the target transceiver when the subscriber transceiver is in the idle mode.

42. (New) A method as in claim 41, wherein the low bandwidth timing signals are transmitted over a non-traffic channel.

43. (New) A method as in claim 41, wherein the subscriber transceiver receives data information from the target transceiver while in the idle mode.

Sub B17  
44.

(New) A method supporting communication of information over a wireless link, the method comprising:

transmitting a data payload over the wireless link from a subscriber transceiver to a base station transceiver using assigned traffic channels;

at the subscriber transceiver, detecting that the data payload has been transmitted to the base station transceiver; and

transmitting a message from the subscriber transceiver to the base station transceiver indicating a request that previously assigned traffic channels be deallocated.

45.

(New) A method as in claim 44, wherein a release of traffic channels results in a subscriber transceiver being placed in an idle mode in which no traffic channels are assigned for use.

AI  
Cont  
46.

(New) A method as in claim 44 further comprising:

at the subscriber transceiver, detecting that the data payload is transmitted to the base station transceiver; and

from the subscriber transceiver, sending a request to release previously assigned traffic channels.

47.

(New) A method as in claim 46 further comprising:

in response to the request to release previously assigned traffic channels, transmitting a message from the base station transceiver to the subscriber transceiver that traffic channels are being deallocated for use.

Sub B17  
Cont  
48.

(New) A system supporting communication of information over a wireless link, the system comprising:

means for storing at least part of a data payload at a subscriber transceiver for transmission over the wireless link to a base station transceiver when no traffic channels are assigned for use;